



SPECIFICATION

WEIFANG SMART POWER GENERATING EQUIPMENT CO.,LTD

Contact: Alicia

Whatsapp:008619106362628

Email:Alicia@appgenset.com

Frequency:60Hz,Voltage:440/254V/1800r/m

Power factor:0.8

Phase:3Ph 4Wr

Protection degree: IP23

Insulation Class: H

Efficiency more than: 85%

Genset Model		Silent Type	WC350GES
Standby Power (KW/KVA)		308/385	
Prime Power(KW/kVA)		280/350	
WEICHAIDiesel Engine	Model		WP10D360E201
	Type		water-cooled, in line, 4-stroke, direct injection,Mechanical pump
	Rated Power(kW)		326
	Aspiration		Turbocharged and aftercooled
	No.of Cylinder		6
	Bore x Stroke(mm)		126x130
	Displacement		9.726
	Compression Ratio		17:1
	Electronic Governor Rate		≤ 1%
	Exhaust Temperature(°C)		489
	Lub oil Capacity(L)		30
	Rated Fuel Consumption75% (L/h)		66.7
Stamford technology Alternator	Model		HC444D
	Standby Power(kW/kVA)		280/350
	Voltage Regulation		≤ ±1
	Excitation Type		Brushless
Controller	Smartgen brand		HGM6110
Fuel tank	sub-base		8hrs working capacity
Overall Size(mm)		Length	3950
		Width	1350
		Height	2050
Gross Weight(kg)		3680	
With battery, battery charger,shock absorber , manual book etc.			

