

CUMMINS 800KVA DIESEL GENERATOR SPECIFICATION



Voltage:230/400/1500r/m

Frequency:50Hz

Power factor:0.8

Phase:3Ph

Protection degree: IP23

Insulation Class: H

Efficiency more than: 85%

Generator passed CE certificate

Generator passed ISO certificate

warranty:one year or 1000running hrs whichever comes first.

Genset Model	Silent Type	CU880GFS
Standby Power (KW/KVA)		704/880
Prime Power(KW/kVA)		640/800
CUMMINS Diesel Engine	Model	KTA38G2B
	Type	water-cooled, in line, 4-stroke, direct injection
	Rated Power(kW)	711
	Aspiration	Turbocharged and aftercooled
	No.of Cylinder	6
	Bore x Stroke(mm)	159x159
	Displacement	38.0
	Compression Ratio	14.5:1
	Noise Level (dBA)	105
	Electronic Governor Rate	≅1%
	Exhaust Temperature(°C)	520
	Lub oil Capacity(L)	151.4
	Rated Fuel Consumption75% (L/h)	155.43
Alternator	Model	HC634C
	Rated Power(kW/kVA)	640/800
	Voltage Regulation	≅±1
	Excitation Type	Brushless
Controller	Deepsea	DSE6120
Parallel cabinet		including
Overall Size(mm)	Length	5800
	Width	2200
	Height	2532
Gross Weight(kg)		10130

Diesel Engine with radiator, copper wire brushless alternator,with fuel tank, Main line circuit breaker,Attenuator silencer, start battery, and other accessories etc.

All technologies are subject to the interpretation of the technology department, subject to change without notice.