

Weifang Smart Power Generating Equipment Co., Ltd.

Address: No. 1316, Liyuan Street, Kuiwen Zone, Weifang City, Shandong province China

CUMMINS 250KW DIESEL GENERATOR SPECIFICATION

		Voltage: 230/400/1500r/m
		Frequency: 50Hz
		Power factor: 0.8
		Phase: 3Ph
		Protection degree: IP23
		Insulation Class: H
		Efficiency more than: 85%
		Generator passed CE certificate
		Generator passed ISO certificate
warranty: one year or 1200 running hrs whichever comes first.		

Genset Model	Silent Type	CU350GFS
Standby Power (KW/KVA)		280/350
Prime Power (KW/kVA)		250/312.5
CUMMINS Diesel Engine	Model	6LTAA9.5-G1
	Type	water-cooled, in line, 4-stroke, direct injection
	Standby Power (kW)	290
	Aspiration	Turbocharged and Charge Air cooled
	No. of Cylinder	6
	Bore x Stroke (mm)	116x148
	Displacement	9.5
	Compression Ratio	16.6:1
	Noise Level (dBA)	75-85
	Electronic Governor Rate	≤ 1%
	Exhaust Temperature (°C)	520
	Lub oil Capacity (L)	28.1
	Rated Fuel Consumption 75% (L/h)	52
Alternator	Model	HC434DH
	Rated Power (kW/kVA)	250/312.5
	Voltage Regulation	≤ ±1
	Excitation Type	Brushless
Controller	Smartgen brand	HGM6120
Fuel tank	sub-base	8hrs working capacity
Overall Size (mm)	Length	3900
	Width	1400
	Height	2050
Gross Weight (kg)		2940

With ATS, battery, battery charger, shock absorber, cummins manual book etc.

All technologies are subject to the interpretation of the technology department, subject to change without notice.